


D6015 Series 60X60X15mm (2.36"X2.36"X0.59")

[View WebPage](#)
[View 3D Object](#)



HOUSING	Thermoplastic PBT, UL94V-0
IMPELLER	Thermoplastic PBT, UL94V-0
BEARING	Sleeve or Ball
OPERATING TEMPERATURE	Sleeve Bearing:-10 °C to +70 °C Ball Bearing:-30 °C to +75 °C
INSULATION RESISTANCE	10 meg Ohms Min.@500 VDC (Between Frame and Terminal)
DIELECTRIC STRENGTH	5 mA Max. at 500 VAC 60Hz for 1 minute (Between Frame and Terminal)
WEIGHT	35g
ROHS COMPLIANCE	Yes

SPECIFICATION

MODEL NO.	RATED VOLTAGE (V)	RATED CURRENT (A)	INPUT POWER (W)	SPEED (RPM)	MAX. AIR PRESSURE		Maximum Air Flow		NOISE dB(A) @1M
					inchH ₂ O	mmH ₂ O	CFM	m ³ /min	
D6015V12H	12	0.18	2.16	4500	0.15	3.90	23.40	0.66	32
D6015V12M	12	0.16	1.92	3800	0.12	3.10	20.22	0.57	30
D6015V24H	24	0.17	4.08	4500	0.15	3.90	23.40	0.66	35.5

DIMENSION

AIR PERFORMANCE

